



Using GLSS modelE

Carlos Cruz

Climate In a Box Workshop

September 21-22, 2010

Goddard Space Flight Center

Greenbelt, MD



Outline

- Introduction to modelE
- Obtaining the code
- Installing modelE: code structure
- Running modelE
- Hands-on



Introduction to modelE

- modelE is a climate model (atmosphere-ocean-sea-ice system) developed at the Goddard Institute for Space Studies (GISS).
- modelE emphasizes an improved physics (tracers, a more resolved stratosphere, cloud microphysics, etc.) over higher resolution.
- Available resolutions are $2^{\circ} \times 2.5^{\circ}$ and $4^{\circ} \times 5^{\circ}$ latitude by longitude.
- Standard vertical resolution is 20 vertical layers (0.1hPa top).



Obtaining the code

- A version of modelE (8/10/2010 snapshot) is already installed and ready to run on the CIB system.
- For in-depth details on how to obtain different code bases and install the model from scratch consult the CIB User's Guide and/or
 - <http://modelingguru.nasa.gov/docs/DOC-1755>
- Generally, on non-NCCS systems contact Gavin Schmidt at:
 - <http://www.giss.nasa.gov/staff/gschmidt.html>



Obtaining the code

- Once registered getting the code is really simple:

```
export CVSROOT=simplex.giss.nasa.gov:/giss/cvsroot
```

```
export CVS_RSH=ssh
```

```
cvs co modelE
```

- This gets you the latest code snapshot.



Configuration

- For modelE to work properly you have to create a configuration file .modelErc in your home directory

```
## Directory structure ##

# DECKS_REPOSITORY - a directory for permanent storage of run info.
# All rundecks that you create will be copied to this directory.
DECKS_REPOSITORY=/home/ccruz2/final/modelEsa/decks

# CMRUNDIR - directory to which all run directories will be linked.
# This directory will be searched by most scripts for locations of
# specific runs.
CMRUNDIR=/home/ccruz2/final/modelEsa/cmrun

# EXECDIR - path to directory with modelE scripts and with some
# executables. This directory should contain the scripts from modelE/exec.
EXECDIR=/home/ccruz2/final/modelEsa/exec

# SAVEDISK - a directory where all run directories (which will contain
# all output files such as rsf, acc etc.) will be created. This should
# be big enough to accomodate all model output.
SAVEDISK=/home/ccruz2/final/modelEsa/out

# GCMSEARCHPATH - directory to search for gcm input files.
# All necessary input files should be copied or linked to this directory.
GCMSEARCHPATH=/cib/inputdata/modelE

# NETCDFHOME - path to location of netcdf library. Leave blank if netcdf
# is not installed on this computer
NETCDFHOME=/cib/libraries/netcdf/3.6.2_intel11

## Customizable settings for Makefile ##
|
# OUTPUT_TO_FILES - if set to YES all errors and warnings will be sent
# to files with the names <source_name>_ERR
OUTPUT_TO_FILES=YES
```

```
# VERBOSE_OUTPUT - if set to YES gmake will show compilation commands
# and some other information. Otherwise most of the output will be
# suppressed
VERBOSE_OUTPUT=YES

# Compiler
COMPILER=intel

# MPI
MPIDISTR=mvapich2
MPIDIR=/opt/mpi/mvapich2/1.5/intel-11.1/bin/..

# ESMF
ESMF=YES
ESMF_COMM=mpich2
ESMF_BOPT=0
ESMFINCLUDEDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/mod
ESMFLIBDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/lib

# openMP
MP=NO
```



Configuration

```
## Directory structure ##

# DECKS_REPOSITORY - a directory for permanent storage of run info.
# All rundecks that you create will be copied to this directory.
DECKS_REPOSITORY=/home/ccruz2/final/modelEsa/decks

# CMRUNDIR - directory to which all run directories will be linked.
# This directory will be searched by most scripts for locations of
# specific runs.
CMRUNDIR=/home/ccruz2/final/modelEsa/cmrun

# EXECDIR - path to directory with modelE scripts and with some
# executables. This directory should contain the scripts from modelE/exec.
EXECDIR=/home/ccruz2/final/modelEsa/exec

# SAVEDISK - a directory where all run directories (which will contain
# all output files such as rsf, acc etc.) will be created. This should
# be big enough to accomodate all model output.
SAVEDISK=/home/ccruz2/final/modelEsa/out

# GCMSEARCHPATH - directory to search for gcm input files.
# All necessary input files should be copied or linked to this directory.
GCMSEARCHPATH=/cib/inputdata/modele

# NETCDFHOME - path to location of netcdf library. Leave blank if netcdf
# is not installed on this computer
NETCDFHOME=/cib/libraries/netcdf/3.6.2_intel11

## Customizable settings for Makefile ##
|
# OUTPUT_TO_FILES - if set to YES all errors and warnings will be sent
# to files with the names <source_name>_ERR
OUTPUT_TO_FILES=YES
```

```
# VERBOSE_OUTPUT - if set to YES gmake will show compilation commands
# and some other information. Otherwise most of the output will be
# suppressed
VERBOSE_OUTPUT=YES

# Compiler
COMPILER=intel

# MPI
MPIDISTR=mvapich2
MPIDIR=/opt/mpi/mvapich2/1.5/intel-11.1/bin/..

# ESMF
ESMF=YES
ESMF_COMM=mpich2
ESMF_BOPT=0
ESMFINCLUDEDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/mod
ESMFLIBDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/lib

# openMP
MP=NO
```

Input data (BCs)

mkdir decks cmrun exec out



Configuration

```
## Directory structure ##

# DECKS_REPOSITORY - a directory for permanent storage of run info.
# All rundecks that you create will be copied to this directory.
DECKS_REPOSITORY=/home/ccruz2/final/modelEsa/decks

# CMRUNDIR - directory to which all run directories will be linked.
# This directory will be searched by most scripts for locations of
# specific runs.
CMRUNDIR=/home/ccruz2/final/modelEsa/cmrun

# EXECDIR - path to directory with modelE scripts and with some
# executables. This directory should contain the scripts from modelE/exec.
EXECDIR=/home/ccruz2/final/modelEsa/exec

# SAVEDISK - a directory where all run directories (which will contain
# all output files such as rsf, acc etc.) will be created. This should
# be big enough to accommodate all model output.
SAVEDISK=/home/ccruz2/final/modelEsa/out

# GCMSEARCHPATH - directory to search for gcm input files.
# All necessary input files should be copied or linked to this directory.
GCMSEARCHPATH=/cib/inputdata/modelE

# NETCDFHOME - path to location of netcdf library. Leave blank if netcdf
# is not installed on this computer
NETCDFHOME=/cib/libraries/netcdf/3.6.2_intel11

## Customizable settings for Makefile ##
|
# OUTPUT_TO_FILES - if set to YES all errors and warnings will be sent
# to files with the names <source_name>_ERR
OUTPUT_TO_FILES=YES
```

```
# VERBOSE_OUTPUT - if set to YES gmake will show compilation commands
# and some other information. Otherwise most of the output will be
# suppressed
VERBOSE_OUTPUT=YES
```

Compiler

```
COMPILER=intel
```

MPI

```
MPIDISTR=mvapich2
```

```
MPIDIR=/opt/mpi/mvapich2/1.5/intel-11.1/bin/..
```

ESMF

```
ESMF=YES
```

```
ESMF_COMM=mpich2
```

```
ESMF_BOPT=0
```

```
ESMFINCLUDEDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/mod
```

```
ESMF_LIBDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/lib
```

openMP

```
MP=NO
```

Compiler and MPI



Configuration

```
## Directory structure ##

# DECKS_REPOSITORY - a directory for permanent storage of run info.
# All rundecks that you create will be copied to this directory.
DECKS_REPOSITORY=/home/ccruz2/final/modelEsa/decks

# CMRUNDIR - directory to which all run directories will be linked.
# This directory will be searched by most scripts for locations of
# specific runs.
CMRUNDIR=/home/ccruz2/final/modelEsa/cmrun

# EXECDIR - path to directory with modelE scripts and with some
# executables. This directory should contain the scripts from modelE/exec.
EXECDIR=/home/ccruz2/final/modelEsa/exec

# SAVEDISK - a directory where all run directories (which will contain
# all output files such as rsf, acc etc.) will be created. This should
# be big enough to accommodate all model output.
SAVEDISK=/home/ccruz2/final/modelEsa/out

# GCMSEARCHPATH - directory to search for gcm input files.
# All necessary input files should be copied or linked to this directory.
GCMSEARCHPATH=/cib/inputdata/modelE

# NETCDFHOME - path to location of netcdf library. Leave blank if netcdf
# is not installed on this computer
NETCDFHOME=/cib/libraries/netcdf/3.6.2_intel11

## Customizable settings for Makefile ##

# OUTPUT_TO_FILES - if set to YES all errors and warnings will be sent
# to files with the names <source_name>_ERR
OUTPUT_TO_FILES=YES
```

```
# VERBOSE_OUTPUT - if set to YES gmake will show compilation commands
# and some other information. Otherwise most of the output will be
# suppressed
VERBOSE_OUTPUT=YES

# Compiler
COMPILER=intel

# MPI
MPIDISTR=mvapich2
MPIDIR=/opt/mpi/mvapich2/1.5/intel-11.1/bin/..

# ESMF
ESMF=YES
ESMF_COMM=mpich2
ESMF_BOPT=0
ESMFINCLUDEDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/mod
ESMFLIBDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/lib

# openMP
MP=NO
```

modelE/config/compiler.intel.mk



Configuration

```
## Directory structure ##

# DECKS_REPOSITORY - a directory for permanent storage of run info.
# All rundecks that you create will be copied to this directory.
DECKS_REPOSITORY=/home/ccruz2/final/modelEsa/decks

# CMRUNDIR - directory to which all run directories will be linked.
# This directory will be searched by most scripts for locations of
# specific runs.
CMRUNDIR=/home/ccruz2/final/modelEsa/cmrun

# EXECDIR - path to directory with modelE scripts and with some
# executables. This directory should contain the scripts from modelE/exec.
EXECDIR=/home/ccruz2/final/modelEsa/exec

# SAVEDISK - a directory where all run directories (which will contain
# all output files such as rsf, acc etc.) will be created. This should
# be big enough to accommodate all model output.
SAVEDISK=/home/ccruz2/final/modelEsa/out

# GCMSEARCHPATH - directory to search for gcm input files.
# All necessary input files should be copied or linked to this directory.
GCMSEARCHPATH=/cib/inputdata/modelE

# NETCDFHOME - path to location of netcdf library. Leave blank if netcdf
# is not installed on this computer
NETCDFHOME=/cib/libraries/netcdf/3.6.2_intel11

## Customizable settings for Makefile ##

# OUTPUT_TO_FILES - if set to YES all errors and warnings will be sent
# to files with the names <source_name>_ERR
OUTPUT_TO_FILES=YES
```

```
# VERBOSE_OUTPUT - if set to YES gmake will show compilation commands
# and some other information. Otherwise most of the output will be
# suppressed
VERBOSE_OUTPUT=YES

# Compiler
COMPILER=intel

# MPI
MPIDISTR=mvapich2
MPIDIR=/opt/mpi/mvapich2/1.5/intel-11.1/bin/..

# ESMF
ESMF=YES
ESMF_COMM=mpich2
ESMF_BOPT=0
ESMFINCLUDEDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/mod
ESMFLIBDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/lib

# openMP
MP=NO
```

modelE/config/mpi.mvapich2.mk



Configuration

```
## Directory structure ##

# DECKS_REPOSITORY - a directory for permanent storage of run info.
# All rundecks that you create will be copied to this directory.
DECKS_REPOSITORY=/home/ccruz2/final/modelEsa/decks

# CMRUNDIR - directory to which all run directories will be linked.
# This directory will be searched by most scripts for locations of
# specific runs.
CMRUNDIR=/home/ccruz2/final/modelEsa/cmrun

# EXECDIR - path to directory with modelE scripts and with some
# executables. This directory should contain the scripts from modelE/exec.
EXECDIR=/home/ccruz2/final/modelEsa/exec

# SAVEDISK - a directory where all run directories (which will contain
# all output files such as rsf, acc etc.) will be created. This should
# be big enough to accomodate all model output.
SAVEDISK=/home/ccruz2/final/modelEsa/out

# GCMSEARCHPATH - directory to search for gcm input files.
# All necessary input files should be copied or linked to this directory.
GCMSEARCHPATH=/cib/inputdata/modelE

# NETCDFHOME - path to location of netcdf library. Leave blank if netcdf
# is not installed on this computer
NETCDFHOME=/cib/libraries/netcdf/3.6.2_intel11

## Customizable settings for Makefile ##

# OUTPUT_TO_FILES - if set to YES all errors and warnings will be sent
# to files with the names <source_name>_ERR
OUTPUT_TO_FILES=YES
```

```
# VERBOSE_OUTPUT - if set to YES gmake will show compilation commands
# and some other information. Otherwise most of the output will be
# suppressed
VERBOSE_OUTPUT=YES

# Compiler
COMPILER=intel

# MPI
MPIDISTR=mvapich2
MPIDIR=/opt/mpi/mvapich2/1.5/intel-11.1/bin/..

# ESMF
ESMF=YES
ESMF_COMM=mpich2
ESMF_BOPT=0
ESMFINCLUDEDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/mod
ESMF_LIBDIR=/cib/libraries/esmf/2.2.2rp3_intel/Linux/lib

# OpenMP
MP=NO
```

Prerequisites for a full installation



Installing modelE: code structure

- Once you get the code you will notice that the code distribution has a top directory – modelE - which contains the following sub-directories:

```
aux  
cmor  
config  
CVS  
decks  
doc  
E2000  
exec  
init_cond  
Makefile  
model  
prtdag  
README  
templates  
tests
```

← Install/run from here

← Scripts

← Model source code

← Experiment templates for rundecks




Installing modelE

cd modelE/decks

- Select a run deck

gmake rundeck RUN=E1M20cib RUNSRC=E1M20



RUNSRC specifies the run deck template

“gmake rundeck” creates a rundeck file E1M20cib.R



Installing modelE

cd modelE/decks

- Select a run deck

gmake rundeck RUN=E1M20cib RUNSRC=E1M20

- Build model

gmake gcm RUN=E1M20cib



"Setup" modelE

cd modelE/decks

- Select a run deck

gmake rundeck RUN=E1M20cib RUNSRC=E1M20

- Build model

gmake gcm RUN=E1M20cib

- Setup model

gmake setup RUN=E1M20cib NCPUS=16



Assumes you are running interactively



Running modelE

- For longer runs edit INPUTZ namelist in E1M20cib.R

```
&INPUTZ  
  YEARI=1949,MONTHI=12,DATEI=1,HOURI=0, IYEARI=1949 ! or earlier  
  YEARE=1949,MONTHE=12,DATEE=2,HOURE=0,      KDIAG=13*0,  
  ISTART=2,IRANDI=0, YEARE=1949,MONTHE=12,DATEE=1,HOURE=1,  
  /
```



```
&INPUTZ  
  YEARI=1949,MONTHI=12,DATEI=1,HOURI=0, IYEARI=1949 ! or earlier  
  YEARE=1954,MONTHE=12,DATEE=1,HOURE=0,      KDIAG=13*0,  
  /
```

- Then re-run “gmake setup” or submit a “job”



Rundecks

- Templates under modelE/templates
- Examples:
 - E1M20 = most basic rundeck

```
modelE 4x5 hor. grid with 20 lyrs, top at .1 mb (+ 3 rad.lyrs)
atmospheric composition from year 1850 (or 1979)      (look below for "_yr") ?
ocean data: prescribed, 1876-1885 (or 1975-1984) climatology (see OSST/SICE) ?
uses turbulence scheme, simple strat.drag (not grav.wave drag)
time steps: dynamics 7.5 min leap frog; physics 30 min.; radiation 2.5 hrs
filters:      U,V in E-W direction (after every dynamics time step)
              sea level pressure (after every physics time step)
```



Rundecks

- Templates under modelE/templates
- Examples:
 - E1M20 = most basic rundeck
 - E1fvcM20: FV cubed-sphere
 - E4M20
 - etc...
- Dozens of templates
- Create your own



CIB hands on

cd /cib/outputdata/guest{X} where $X=1...9$

cp /cib/inputdata/archives/modelE.scratch.tgz . ← Note the space followed by a dot



CIB hands on

cd /cib/outputdata/guest{X} where $X=1...9$

cp /cib/inputdata/archives/modelE.scratch.tgz .

tar xfz modelE.scratch.tgz

cd modelE.scratch



CIB hands on

cd /cib/outputdata/guest{X} where X=1...9

cp /cib/inputdata/archives/modelE.scratch.tgz .

tar xzf modelE.scratch.tgz

cd modelE.scratch

cp /cib/models/archives/modele_env.bash .

. ./modele_env.bash ← This script will set the module environment



Note the space followed by a dot



CIB hands on

```
cd /cib/outputdata/guest{X} where X=1...9
```

```
cp /cib/inputdata/archives/modelE.scratch.tgz .
```

```
tar xfz modelE.scratch.tgz
```

```
cd modelE.scratch
```

```
cp /cib/models/archives/modele_env.bash .
```

```
./modele_env.bash
```

```
./setupmodelE
```



This script will copy modelE and generate .modelErc



CIB hands on

ls modelE

aux config decks E2000 init_cond model README tests
cmor CVS doc exec Makefile prtdag templates

Open up `~/modelErc` with your favorite editor



CIB hands on

```
cd modelE/decks
```

```
cp /cib/models/archives/modele_run.j . ← Note the space followed by a dot
```



CIB hands on

cd modelE/decks

cp /cib/models/archives/modele_run.j .

- Edit modele_run.j: change X to number from 1...9



CIB hands on

cd modelE/decks

cp /cib/models/archives/modele_run.j .

- Edit modele_run.j: change X to number from 1...9
- When done **submit** the “job” to the batch system. To **submit** the job we use the “qsub” command:

qsub modele_run.j

- You can monitor the job via the “qstat” command:

qstat



CIB hands on

- Results will be in out directory. So

cd /cib/outputdata/guestX/modelE.scratch/out/E1M20test

Open up file *E1M20test.PRT*, look at bottom for:

>> Terminated normally (reached maximum time) <<

- Output can be viewed with GrADS or Panoply (both installed on CIB system).




Questions?



A climate sensitivity experiment

- Ref: <http://modelingguru.nasa.gov/docs/DOC-1757>
- Set up a $2xCO_2$ sensitivity experiment using E4M20
 - Restoring run
 - Q-flux adjusted Control run
 - $2xCO_2$ perturbation run



$$\rho c_p h \frac{\partial T}{\partial t} = S_{\downarrow} (1 - \alpha) + F_{\downarrow} - F_{\uparrow} - SH - LH$$



References

- Configurations for AR4 Simulations:
 - GISS-ER: ModelE20/Russell $4\times 5\times L20$ (This corresponds to the rundeck E1aoM20.R)
 - GISS-EH: ModelE20/HYCOM $4\times 5\times L20$
 - Sun, S., and R. Bleck, 2006: Multi-century simulations With the coupled GISS-HYCOM climate model: Control experiments. *Clim. Dyn.* 26, 407-428. DOI 10.1007/s00382-005-0091-7
 - GISS-AOM: (C4 \times 3)
- Model documentation, including the ModelE specification and results from three standard configurations, is given in the following journal article:
 - Schmidt, G.A., et. al. 2006. Present day atmospheric simulations using GISS ModelE: Comparison to in-situ, satellite and reanalysis data. *J. Climate* 19, 153-192.